

Submersible Chopper Pumps SPB



PATENT PENDING



EFFICIENT, COMPACT, VERSATILE

CHIOR® SPB-type Submersible Chopper Pumps are designed for shredding and lifting slurry from animal husbandry, biogas digestate or industrial wastewater containing lumpy and fibrous solids. The highly efficient size reduction of the fibrous components in the material is caused by an innovative cutting system that ensures optimum pump operation even under harsh working conditions.

Its compact design and reduced overall dimensions make the pump easy to handle and install. The SPB range is available with a variety of accessories suitable for multiple applications. The CHIOR® SPB submersible chopper pumps can be installed horizontally in various configurations, either fastened to a vertical pole fixed to the tank or free-standing on the bottom of the tank.




Horizontal pole-mounted installation



Free-standing horizontal installation

Technical Data and Overall Dimensions



Type	Power Installed (kW)	Dimensions (mm)		DN	Weight (kg)
		A	B		
SPB 022	2.2	615	405	80	95
SPB 030	3.0				98
SPB 040	4.0				105
SPB 055	5.5	765	460	100	150
SPB 075	7.5				165
SPB 110	11.0	920	575	150	260
SPB 150	15.0				265
SPB 185	18.5				275
SPB 220	22.0				295

Benefits

- ✓ **High-efficiency, low-energy consumption electric motor**
- ✓ **Innovative, efficient chopping system preventing clogging**
- ✓ **Self-adjusting chopping system**
- ✓ **Anti-leakage design for extended durability**
- ✓ **Easy maintenance thanks to modular chopping unit design**

Technical Features





- **Innovative chopping system** allows multiple cutting points per rotation
- Direct contact between sharpened helicoid blades and fixed knives ensuring optimum shredding
- La bocca di aspirazione aperta permette il deflusso del materiale in eccesso e previene intasamenti

PATENT PENDING

SPB DN 80-100



SPB DN 150



- Cast iron body
- Submersible IE3 electric motor (Premium Efficiency)
- 3-phase, 4-pole, insulation class F, IP68 protection motor
- Thermal probe preventing motor from overheating

- Fixed knives, helicoid and impeller blades manufactured from treated and hardened material
- Mechanical silicon carbide seal
- Rubber-sheathed cable with stainless-steel cable gland

Accessories




Mounting kit for horizontal free-standing installation




Bracket mounting kit for horizontal pole-mounted installation

Product Range Performance

SPB 11 - 22 kW



SPB 2,2 - 7,5 kW



* Values measured with clear water at 20 °C.

Results may vary by changing the operating conditions depending on the flow rate, density and viscosity of the liquid, the type and dry matter content of the slurry (depending on type of animal feed), the height and distance of the support, as well as the diameter of the pipe.

Application

